



PRODUCT/MATERIAL: Clay

MANUFACTURER / DISTRIBUTOR: LAGUNA CLAY COMPANY
 ADDRESS: 14400 Lomitas Avenue, City of Industry, CA 91746
 PHONE / FAX/ E-MAIL: (626) 330-0631 / (626) 333-7694 / MSDS@Lagunaclay.com

SECTION I – PRODUCT IDENTIFICATION

TRADE NAME: Moist Clay
 SYNONYM: Laguna Moist Clay
 CHEMICAL FAMILY: Not Applicable

SECTION II – HAZARDOUS INGREDIENTS

INGREDIENT NAME	CAS NUMBER	EXPOSURE LIMITS
Crystalline Silica (Quartz)	14808-60-7	Respirable Quartz: OSHA PEL: TWA-TLV= 0.1mg/m ³ , ACGIH TLV= 0.1mg/ ³ , NIOSH TWA: = 0.05 mg/. m ³

THERE ARE EXTREMELY SMALL, BUT DETECTABLE AMOUNTS OF SUBSTANCES REGULATED UNDER CALIFORNIA'S SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65).

None.

THESE LEVELS ARE "TYPICAL QUANTITIES" AND MAY CHANGE SLIGHTLY WITH DIFFERENT LOTS. THE TERM "LESS THAN OR TRACE AMOUNT" INDICATES THAT THE SUBSTANCE WAS DETECTED, BUT THE AMOUNT WAS LESS THAN THE QUANTIFIABLE LIMIT.

SECTION III – PHYSICAL DATA

BOILING POINT (°F)	Not Applicable
VAPOR PRESSURE	Not Applicable
VAPOR DENSITY	Not Applicable
SOLUBILITY IN WATER	Insoluble
SPECIFIC GRAVITY	1.7 – 3.7
PERCENT VOLATILE BY WEIGHT	0
EVAPORATION RATE	0
APPEARANCE AND ODOR	Color varies between moist and dry state; no odor.

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	Not Flammable
EXTINGUISHING MEDIA	Water
UNUSUAL FIRE OR EXPLOSION HAZARDS	None
SPECIAL FIRE FIGHTING PROCEDURES	None

SECTION V – REACTIVITY DATA

STABILITY FACTOR	Product is stable.
INCOMPATIBILITY	None
HAZARDOUS DECOMPOSITION PRODUCTS	None. Hazardous polymerization will not occur.
CONDITIONS TO AVOID	Inhalation of dust.

SECTION VI – HEALTH HAZARD DATA

CARCINOGENICITY	This product contains crystalline silica; there is evidence of delayed respiratory disease (silicosis) if inhaled over a long period of time. IRAC, NTP, and California Proposition 65 conclude that inhaled crystalline silica causes cancer. This product contains a small amount of Titanium Dioxide as a natural part of the clay's composition. This has been listed by NIOSH as a potential carcinogen. Respirable Quartz: OSHA PEL: TWA-TLV = 0.1mg/m ³ , ACGIH TLV=0.1mg/m ³ , NIOSH TWA =0.05 mg/ m ³ .
PRIMARY ROUTES OF ENTRY	Inhalation (dry form only), ingestion and dermal.
SUMMARY OF RISKS	Individuals with a lung disease/condition (e.g.: bronchitis, emphysema, chronic pulmonary disease) can be aggravated by exposure
EMERGENCY FIRST AID	No specific first aid is necessary since the adverse health effects associated with this compound results from chronic exposures.
Eye Contact:	May be an irritant, flush eyes with generous amounts of water for at least 15 minutes; call a physician if irritation persists.
Skin Contact:	May cause local dermatitis, which is relieved when removed.
Ingestion	Toxicity due to ingestion is low.
Inhalation	Remove to fresh air, call a physician if irritation due to inhalation persists.
Physician's Note	None

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Spills or Release Procedure	Follow normal clean-up procedures. Care should be taken to avoid causing dust to become airborne. Vacuum or use wet clean-up techniques.
Waste Disposal Procedure	Dispose material in accordance with Federal, State, and Local regulations.

SECTION VIII – CONTROL MEASURES

Provide adequate ventilation to keep dust or vapor concentrations below acceptable exposure limits. Use gloves as needed for handling material containers. Wear safety glasses when needed. Appropriate respiratory protection may be required to protect from certain dusts. Respirators must be selected and used in accordance with OSHA Subpart 1 (29 CFR 1910.134).

SECTION IX – TOXICOLOGICAL INFORMATION

This product (and all of it's components) is in compliance with the U.S. EPA 15 U.S. C. 2604 regulation. If your product is a glaze; Laguna Clay Company liquid glazes are certified as NON-TOXIC, and conform to ASTM D-4236 and C-1023 under the federal Labeling of Hazardous Art Materials Act (LHAMA). Specific Toxicology information on materials is available upon request.

SECTION X – REGULATORY

This product may contain materials that require reporting under Section 313 of the Emergency Planning and Community Right-To-Know Act (Superfund Amendments and Reauthorization Act (SARA)), and 40 CFR Part 372. SARA TITLE III Data: None.

**SECTION XI – DISCLAIMER**

The information provided in this MSDS document has been provided to Laguna Clay Company by its material suppliers and is represented by those suppliers as accurate and reliable. Laguna Clay Company is not liable for injury, loss, or damage, direct or consequential, arising out of the use or inability to properly use this product. This product is intended only for use in traditional ceramic applications.

This MSDS conforms to the ASTM D-4236 and C-1023 requirements defined by LHAMA, the Federal Labeling of Hazardous Art Materials Act. LHAMA was developed by the American Society of Testing and Materials (ASTM) to ensure the proper labeling of art materials.