

# MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION  
**OCT 24 1989**      AMO-1

FOR COATINGS, RESINS AND RELATED MATERIALS  
(Approved by US Department of Labor "Essentially Similar" to Form OSHA-20)

NPCA 1-72  
100687

## Section 1

American Art Clay Co., Inc.  
Reward Ceramic Color Mfrs., Co.  
4717 W. Sixteenth Street  
Indianapolis, IN 46222

EMERGENCY TELEPHONE NO.:  
(317) 244-6871, (800) 428-3239, (800) 358-8252.  
or contact your local poison control center.  
TELEX 272145 AMACO IND

PRODUCT CLASS: Ceramic Product in Liquid      TRADE NAME: AMACO  
Packaging: 1 Pt., 1 Gal.

MANUFACTURERS CODE IDENTIFICATION:  
Plaster Separator.      Gum Solution.

## Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	PPM	TLV mg/M3	LEL	VAPOR PRESSURE
NO HAZARDOUS INGREDIENTS  NON-TOXIC  BEARS THE AP SEAL	100%	N/A	N/A	N/A	N/A

## SPECIAL LABELING INSTRUCTIONS

American Art Clay Co., Inc./Reward Ceramic Color Mfrs., Co. is a member of the Art and Craft Material Institute, 715 Boylston St., Boston MA 02116. Our art and craft materials are certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 (American Society for Testing and Materials). This product is appropriately labeled with one of the following nontoxic seals:



"Products bearing the Certified Products Seal or the AP Approved Product Seal of The Art Craft Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute's Toxicological Advisory Board to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems.

In addition, products bearing the CP Seal meet specific requirements of materials, workmanship, working qualities and color described in the appropriate Product Standard issued by The Art and Craft Materials Institute, Inc. or other recognized standards organization."

## Section III - PHYSICAL DATA

BOILING RANGE:  NOT APPLICABLE

VAPOR DENSITY:  NOT APPLICABLE,  HEAVIER,  LIGHTER, THAN AIR

EVAPORATION RATE:  NOT APPLICABLE,  
 FASTER,  SLOWER, THAN ETHER

PERCENT VOLATILE  
BY VOLUME: 0.0

SPECIFIC GRAVITY:  
Less Than 2

## Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: None

FLASH POINT:  NOT APPLICABLE

LEL: N/A

EXTINGUISHING MEDIA:  NOT APPLICABLE - no fire or explosion hazard

UNUSUAL FIRE AND EXPLOSION HAZARDS:  NONE

SPECIAL FIRE FIGHTING PROCEDURES:  NONE

**Section V - HEALTH HAZARD DATA**

THRESHOLD LIMIT VALUE: Non-toxic carries the AP Seal. Labeling conforms to ASTM D-4236. TLV has not been established for the whole product.

EFFECTS OF OVEREXPOSURE:

None.

EMERGENCY AND FIRST AID PROCEDURES:

Not applicable. Non-toxic. If in doubt, contact your local poison control center.

**Section VI - REACTIVITY DATA**

STABILITY:  UNSTABLE  STABLE

CONDITIONS TO AVOID: None.

INCOMPATIBILITY (materials to avoid):

None.

HAZARDOUS DECOMPOSITION PRODUCTS:

None.

HAZARDOUS POLYMERIZATION:  MAY OCCUR  WILL NOT OCCUR

CONDITIONS TO AVOID: None.

**Section VII - SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Clean with a paper towel or wet sponge. Wash with soap and water.

WASTE DISPOSAL METHOD:

Dispose of paper towel in trash and rinse wet sponge.

**Section VIII - SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:

Not needed.

VENTILATION:

Not needed.

PROTECTIVE GLOVES: Not needed.

EYE PROTECTION: Not needed.

OTHER PROTECTIVE EQUIPMENT: Not needed.

**Section IX - SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Always keep lid tightly on jar while in storage. Uncovered the product will dry out.

OTHER PRECAUTIONS:

None.